

# For Controlled Concentrated Heating

# **Model 5420**



# FAST. CONTROLLED.

#### **Precision Control For:**

SpotIR®

LineIR®

StripIR®

## Model 5420 ControlIR®

The Model 5420 ControllR is a **15 amp** power controller designed to control the voltage supplied to many of the Research, Inc. heaters. It is available in **120**, **240**, and **480** volt versions and may be ordered with a manually set potentiometer, a potentiometer and timer, or receptacle to accept a 4 to 20mA external control signal.





#### For Controlled Concentrated Heating.

## **FAST. CONTROLLED.**

#### Features and Benefits Controller Model 5420

- Phase angle fired SCR provides precise voltage to heaters.
- Plug and 8 foot long power cord plugs into power receptacle.
- 120, 240, and 480 volt models (at 15 Amps) match all listed Research, Inc. heaters.
- Potentiometer, timer, and external run signal options allow user to select the method for controlling the voltage.
- Compact size keeps space required for the controls to a minimum.

## **Product Description Controller Model 5420**

All Model 5420 ControllRs have a power cable and plug to connect to a wall receptacle and a terminal block to terminate the wires coming from the heater. They all use a phase angle fired SCR to control voltage.

#### **CONTROLLERS**

#### Model 5420 Power Controller

The Model 5420 Power Controller has an off/on switch and a manual potentiometer that will vary the output voltage from 0% to 97% of the line voltage.

#### Model 5420E Power Controller

The Model 5420E Power Controller has an off/on switch, a manual potentiometer that will vary the output voltage from 0% to 97% of the line voltage and a timer. The timer has a 50 increment dial and may be set to adjust the voltage and a timer. The timer has a 50 increment dial and may be set to adjust the voltage from 0 to 5.0 seconds, 0 to 5.0 minutes, 0 to 50 minutes, 0 to 5 hours, or 0 to 50 hours.

#### Model 5420mA Power Controller


The Model 5420mA Power Controller has and off/on switch and a receptacle/plug to accept a 4 to 20mA control signal from an external source to regulate the output voltage from 0% to 97% of the line voltage..





# For Controlled Concentrated Heating.

# **Product Drawings - Controller 5420**





# For Controlled Concentrated Heating.

# **How to Order - Controller 5420**

PRODUCT SPECIFICATIONS			
Description	120 volt, 15 Amp	240 volt, 15 Amp	480 volt, 15 Amp
Manual Potentiometer	Model 5420-120	Model 5420-240	Model 5420-480
Manual Potentiometer and Timer	Model 5420E-120	Model 5420E-240	Model 5420E-480
4 to 20mA external control	Model 5420mA-120	Model 5420mA-240	Model 5420mA-480